

MIC-712P-ON

AI Platform Based on NVIDIA® Jetson Orin™ Nano

Preliminary



Features

- Ultra-slim design for mobile equipment in safety & security applications
- Embedded with NVIDIA® Jetson Orin™ Nano
- Support 6 ports POE with 25W supply per port.
- Support NVIDIA super mode up to 67 TOPS performance
- Integrate Out-of-Band management within the system




Specifications

		NVIDIA® Jetson Orin™ Nano
Processor System	CPU	8GB: 6-core NVIDIA Arm Cortex A78AE v8.2 64-bit CPU 4GB: 6-core NVIDIA Arm Cortex A78AE v8.2 64-bit CPU
	GPU	8GB: 1024 core NVIDIA Ampere GPU with 32 Tensor Cores 4GB: 512 core NVIDIA Ampere GPU with 16 Tensor Cores
	Memory	8GB: 8GB LPDDR5 4GB: 4GB LPDDR5
I/O	Ethernet	2 x 10/100/1000 Mbps 6 x 10/100/1000 Mbps POE. Support 30W per port, individual control, total power budget 150W
	Display	HDMI (Max. resolution 3840x2160 @ 60Hz)
	USB	External: 4 x USB 3.2 Gen 2
	Debug console	1 x Micro USB
	OTG USB	1 x Micro USB
Expansion	M.2 E-key	1 x 2230 E-key (Signal: PCIe + USB 2.0)
	M.2 B-key	1 x M.2 3052 (Signal: USB3.2)
	SIM	1 x Nano SIM slot 1 x eSIM (Optional)
	TPM (Optional)	1 x TPM 2.0
Storage	M.2	1 x M.2 2280 (Signal: PCIe x4) pre-installed 128G SSD
	SD Card	1 x Micro SD
Power	Mode	AT
	Input Voltage	19 ~ 36 V _{DC}
Environment	Operating Temperature	-25 ~ 70 °C with 0.7 m/s airflow
	Operating Humidity	95% @ 40 °C (non-condensing)
	Vibration	3 Grms @ 5 ~ 500 Hz, random, 1 hr/axis
	Shock	10G / 11ms
Mechanical	Dimensions (W x D x H)	160 x 160 x 70 mm (6.3" x 6.3" x 2.76")
	Weight	2.05 kg (w/o packing material)
	Installation	Desktop
BSP	Jetpack	JP6.2 or above
Certifications		CE/FCC/UKCA/CB/UL/BSMI/CCC (No RED certification)

Dimensions

Unit: mm



Ordering Information

Part Number	NVIDIA Module	NVIDIA Module Memory	NVIDIA Module eMMC	NVMe**	BSP version	Super mode support
MIC-712P-ON3A1	Orin Nano	8GB	N/A	128GB	Jetpack 6.2	Yes
MIC-712P-ON2A1	Orin Nano	4GB	N/A	128GB	Jetpack 6.2	Yes

** The system BSP will be pre-installed in a 128GB NVMe M.2 SSD.

Packing List

Part Number	Description	Quantity	Part Number	Description	Quantity
MIC-712P-ON	MIC-712 Fanless system	1	1930005673-11	Screw M3x4.5L for Peripheral	2
1652002202	Power connector - 2-pin	1	1960095312N001	Mounting Bracket	2
1700023619-01	Micro USB cable for System recovery	1	1930007979	Screw for mounting bracket	4

Optional

	Part Number	Description	Quantity
5G	AIW-356-DQ	5G Sub6+GNSS M.2 3052 Key B (by region)	1
	1751000809-01	RF Cable SMA/F/RA MHF4L/113 BLK L250mm	4
	1750009372-01	Ant.SMA/M 90/180 5G BLK 167mm RG178 (5G)	4
AC/DC Adapter	XMIC-FSP230-AAAN3	ADP A/D 100-240V 230W 24V C14 TERMINAL BLOCK 2P	1
Power Cord	1702002600	Power Cord UL 3P 15A 125V C13 183 cm (US)	1
	1702002605	Power Cord EU 3P 10A 250V C13 183cm (EU)	1
	1702031801	Power Cord BSI 3P 10A 250V C13 183cm (UK)	1
	1700029019-01	Power Cord (PSE/BSMI), 3-pin, 7A, 125V, 1.8 M, DAC-ST01	1
	1700000596-11	Power Cord CCC 3P 10A 250V C13 183cm (China)	1
TPM	PCA-TPMSPI-00A1	PCA-TPMSPI-00A1	1
Cable	1700027920-01	Audio port cable (1 x Line-In + 1 x Mic)	1