

2U Intel Xeon 6 Rackmount System

VELA-SVR-EP9-4U-9335

A flexible 4U AMD server platform for data processing, virtualisation, networking and other performance-intensive workloads. Built around the Advantech ASMB-831T2 server motherboard, the system features a 5th Gen AMD EPYC 9335 processor with 32 cores, 64 threads, speeds up to 4.4GHz and 128MB L3 cache. Its 4U rackmount chassis includes four hot-swap 3.5"/2.5" SAS/SATA drive bays, flexible expansion for networking, storage and I/O, and IPMI remote management, with configurable memory, storage, networking, expansion and operating system options.



IMPULSE EMBEDDED LIMITED

Unit 1, Beata Road, Newcastle-under-Lyme, Staffordshire, United Kingdom, ST5 7UT
Tel: +44 (0)1782 337 800 Fax: +44 (0)1782 337 801 Email: sales@impulse-embedded.co.uk
Website: www.impulse-embedded.co.uk

Standard Configurations

This specification sheet covers both standard variants. Differences are shown side by side. Shared specifications apply to both models, unless stated otherwise.

Specification	VELA-SVR-EP9-4U-9335
Processor	AMD EPYC 9335
Cores / Theads	32/64
All Core Boost	4GHz
Cache	128MB
Memory	64GB (4x 16GB) 5600MHz LRDIMM CL46
Storage	1TB NVMe PCIe Gen4 x4 SSD, 112-layer 3D NAND flash
System Core	
Motherboard	ASMB-831T2-00A1, Industrial Grade ATX Serverboard
Chipset	AMD
CPU Socket	AMD LGA 6096 (Socket SP5)
Supported CPU Power	Up to 300W
Chassis	HPC-7442MB-00XE 4U rackmount chassis
Power Supply	500W ATX 80 Plus Bronze power supply
Graphics	Onboard/Server Management Graphics

System Specification

Specification	VELA-SVR-EP9-4U-9335
I/O	
Ethernet	2x 10GbE, 1x Dedicated GbE Management Port
Display	1x VGA
USB Rear	4x USB3.2 Gen1
USB Front	2x USB2.0 Front
Serial	1x RS-232
Storage & Expansion	
M.2	1x M.2 2280/22110 (PCIe Gen4/SATA), 1x M.2 2280/22110 (PCIe Gen4)
Drive Bays	4x Hot-swap 3.5"/2.5" SAS/SATA HDD trays*; 1x 3.5" Internal Drive Bays; 1x Slim Optical *upgrade to 8x Hotswap with expansion kit
RAID	-
PCIe	5x PCIe Gen5 [x16]; 2x PCIe Gen5 [x8]
PCI	-

System Specification

Specification	VELA-SVR-EP9-4U-9335
Security & Remote Management	
IPMI	Yes
TPM	Built-in firmware TPM (fTPM)
Security	AMD Infinity Guard
Mechanical & Environmental	
Dimensions (W x H x D)	482 x 177 x 600
Operating Temperature	0°C to +40°C
Mounting	Rackmount - Slide Rails Ordered Separately
Warranty	3 Years Return to Base


Ordering Information

Model	Processor	Memory	Storage
VELA-SVR-EP9-4U-9335	AMD EPYC 9335	64GB	1TB

Configuration note: The specification above defines the standard orderable VELA-SVR-EP9-4U-9335 system. Alternative configurations are available and can be discussed separately. All specifications are subject to change without notice. Please visit our website for the most up to date product information.

Mechanical Specification

Dimensions



IMPULSE EMBEDDED LIMITED

Unit 1, Beata Road, Newcastle-under-Lyme, Staffordshire, United Kingdom, ST5 7UT

Tel: +44 (0)1782 337 800 Fax: +44 (0)1782 337 801 Email: sales@impulse-embedded.co.uk

Website: www.impulse-embedded.co.uk